Apix 601 Industrial Label Printer

High functionality and multiple connectivity

The **Apix 601 industrial label printer** presents itself as an excellent printing solution when the work environment is hectic and difficult such as warehouses, distribution centers, as well as stores and healthcare facilities. The machine is capable of producing high volume barcode labels with maximum speed

COD: STTTAP018
PLURISERVICE CODE STTTAP018

Retail | Trasporti e logistica | Produzione | Sanità | Fashion

DESCRIPTION

Apix 601: high performance for cutting-edge companies

The **Apix 601 industrial label printer**, featuring the same design as the Apix 251, can print on bases up to 6.8″. An ideal product for warehouse, logistics, manufacturing, healthcare and retail operations.

Speed and ease of use are two key features of this powerful machine, which can **print high volume labels extremely quickly**. The Apix 601 presents itself as a key ally for all companies seeking printing solutions that enable them to respond to ever-increasing operational complexities.

Ease of management and use

The printer offers the ability to take advantage of **dynamic remote management** of multiple functions of the printing process, thereby reducing downtime and maintenance costs.

The color LCD display also allows direct control of some printer functions and printhead and roller replacement are extremely simple operations.

TECHNICAL SPECIFICATIONS

Printing method: Thermal Transfer and Direct Thermal
Max. print speed: 305 mm/second
Max. print width: 168 mm
Max. print length: 14.732 mm
Dimensions: 357 x 313 x 514 mm
Weight: 17,80 kg
Label roll capacity: 208,3 mm
Ribbon: 450 m (lenght) – 50,8 mm ~ 178 mm (width)
Processor: 32-bit RISC CPU
Memory: 512 MB Flash memory, 256 MB SDRAM, microSD Flash memory card reader for Flash memory expansion, up to 32 GB
Interface: RS-232**,** Parallel, USB 2.0 (high speed mode), internal Ethernet, 10/100 Mbps,USB host *2 (front side), GPIO (DB15F) (dealer option), Slot-in 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (dealer option)
Display: 4.3” color display, 480 x 272 pixel; Resistive touch screen