



# Pluricode 201 Thermal Label Printer

## Modern design and high-speed printing

The Pluricode 201 thermal label printer, with its modern design and faster printing speed of up to 6 inches (152 mm/s), will enhance your daily efficiency. Its 8MB SDRAM and 8MB Flash memory provide greater flexibility for various uses.

COD: STTTPC010

PLURISERVICE CODE STTTPC010



Retail



Sanità

## DESCRIPTION

### Pluricode 201 Thermal Label Printer: Modern and Efficient

The Pluricode 201 is a 4" thermal label printer designed to deliver high efficiency and reliability even in demanding work environments. Thanks to its robust construction and a maximum printing speed of 152 mm/s, it is perfectly suited for industrial settings, warehouses, and retail points of sale where precision and speed are essential.

The printer can operate smoothly within a temperature range of 5°C to 40°C, making it ideal for environments with varying conditions. Equipped with advanced technology and easily integrable into existing business systems, the Pluricode 201 is the optimal choice for those needing a reliable and long-lasting solution for high-productivity label printing.

## TECHNICAL SPECIFICATIONS

### PRINTING

- Printing method: Direct thermal
- Maximum printing speed: 152 mm (6") / s
- Maximum print width: 104 mm (4.25")

### MEDIA

- Media type: Continuous, with gap, black mark, fan-fold, and perforated hole
- Media width: 25.4 mm ~ 118 mm (1.0" - 4.6")
- Label length: 10 mm ~ 1778 mm

### PERFORMANCE

- Processor: 32-bit CPU
- Memory: 8MB Flash, 8MB SDRAM, Flash memory expandable up to 4GB
- Interface: Standard: USB
- Optional: LAN/WiFi/Bluetooth/TF card
- Sensors: Gap sensor, cover open sensor, black mark sensor

### PHYSICAL SPECIFICATIONS

- Dimensions: 215 mm (L) x 178 mm (W) x 149.5 mm (H)
- Weight: 1.32 kg