

Automatic label applicator LPA.430

Quick and Precise Labeling on Moving Products.

LPA.430 applicator is the answer. Designed for businesses that can't afford interruptions, this high-frequency linear labeling system is designed to seamlessly integrate your production line, ensuring the highest application quality on every product on the go. It's not just about applying labels: it's about optimizing your processes and ensuring flawless traceability.

COD:

PLURISERVICE CODE PSG-LPA.430S.AF



DESCRIPTION

- Speed and Accuracy: With an application speed of up to 30 m/min, the LPA.430S handles large volumes while maintaining absolute precision. Its ability to label products sequentially and on the go makes it ideal for dynamic manufacturing environments.
- Maximum Adaptability: This applicator works with a wide range of materials, including labels on coated, glossy, metallic and thermal paper, offering unparalleled versatility. Supports label widths from 25.4mm to 118mm, adapting to your specific needs.
- Intuitive Control: The backlit TOUCH color display makes for immediate use. You can easily adjust distribution speed, label feed and counters with a simple tap. The password-protected menu allows you to save up to 40 programs, ensuring rapid production changes and operational security

TECHNICAL SPECIFICATIONS

- Supporti utilizzabili: Etichette in rotolo, carta patinata, lucida, carta metallizzata, carta termica.
- Dimensioni rotolo etichette: Ø interno 42 / 76 mm - Ø esterno 345 mm
- Larghezza min max. etichette: da 25,4 mm a 118 mm
- Velocità di applicazione: Fino a 30 m/min.
- Massima trazione rotolo etichette: Kq.10
- **Peso:** kg 38 circa.
- Alimentazione di rete: 220 Volt 50Hz.
- Dimensioni ingombro: Larghezza 900 mm Altezza. 540 mm Prof. 350 mm