



Color printer OKI P1050

Innovation in label printing

The **OKI P1050** is the ideal solution for companies that need low-run label printing with a high mix of variants. Designed to offer maximum flexibility, this color printer (pentachrome) allows you to produce high-quality labels on demand, without the need for pre-printed stock.

Why choose the OKI P1050?

The Power of White: Unlike common printing devices, the P1050 includes the fifth color (white). This allows you to create stunning food, beverage, and cosmetic labels on metallic, dark, or clear materials.

Maximum Versatility of the Supports: No special expensive supports are needed. You can print on plain paper, synthetic film, PET and glossy labels with thicknesses from 0.076 to 0.250 mm.

Efficiency and Speed: With a print speed of up to 152.4 mm/s (6 ips) and a resolution of 1200 x 1200 dpi, you achieve professional results in record time.

Simplicity of Use: Featuring a complete automatic cutting system and intuitive roll management, the P1050 is ready to integrate into your Windows workflows.

COD: STTTOK006

PLURISERVICE CODE



Retail



Trasporti e logistica



Fashion

OPERATING SYSTEMS



Android

DESCRIPTION

Revolutionize your in-house production with the **OKI P1050**, the digital electrophotographic printer that brings color printing innovation right to your business. With the addition of white toner, you can print bright graphics on transparent or dark media, eliminating the limitations of traditional machines and reducing the total cost of ownership.

TECHNICAL SPECIFICATIONS

- **Print speed:** Max 152.4 mm/s (6 ips)
- **Printing technology:** 5-bar full pentachrome digital electrophotographic printing method LED.
- **Print resolution:** 1200 x 1200 dpi, 600 x 600 dpi
- **Media format:** Roll.
- **Holder Width:** Paper Roll: 25.4mm (1.0")- 130mm (5.1") liner included.
- **Label length per process:** 12.7 mm - 1320.8 mm
- **Print width:** 25.4 mm - 125.76 mm (4.95").
- **Cutting length:** Min. 101.6 mm (4").
- **Media type:** Plain paper, film, label on plain paper, label on glossy paper, label on synthetic film, label on film (PET).
- **Support thickness:** 0.076 - 0.250 mm
- **Automatic cutting:** full cutting.
- **Print languages:** Adobe PostScript3, PCL 5c emulation, PCL 6 (XL) emulation.
- **Power supply:** Single phase 230V AC

+/-10%, 50/60 Hz +/-2%.

- **Size (LxAxP):** 1040 x 477 x 441 mm.
- **Weight (including consumables):**
Approximately 62 kg (printer with unwinder)
- **Weight (consumables excluded):**
Approximately 50 kg (printer with unwinder).
- **Supported operating systems:**
Windows 10, Windows 8.1, Windows 8, Windows 7, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012, Windows Server 2008 R2, Windows Server 2008.