



Pluricode 300 barcode Printer

direct thermal and thermal transfer printing technology

The **Pluricode 300 barcode printer** is a **desktop printer** that offers great printing performance at a low cost. Prints labels at 5 "per second and supports ribbons up to 300 meters.

COD: Pluricode300

PLURISERVICE CODE STTTPC001



Retail



Trasporti e
logistica



Produzione



Sanità



Fashion

DESCRIPTION

Great performance and excellent price

The Pluricode 300 barcode printer is a label printer with direct thermal and thermal transfer printing technology.

It is small and light. The weighs is only 2.26 kg and the volume is little (285 L x 226 P x 171 H mm).

Small dimensions, but high level performances.

The Pluricode 300 barcode printer prints labels at a speed of 5" per second and supports a wide range of labels.

The Pluricode 300 barcode printer withstands large print volumes thanks to the dual-wall frame, robust and sturdy structure.

Pluricode 300 supports ribbons up to 300 meters to work well and for a long time.

The maximum printing width is 108 mm, while the printing length starts from 15 mm.

The Pluricode 300 barcode printer is a winner both in terms of performance and price

TECHNICAL SPECIFICATIONS

PRINTING

Printing Method: Thermal transfer/Direct thermal

Resolution: 203dpi(8dots/mm)

Printing Speed: 5IPSM_{max}

Printing Width: 108mm Max

Printing Length: from 15mm

PROCESSOR: 32 bit RISC CPU

MEMORY

RAM: 32 MB

Flash: 16 MB

DETECTION

Sensors: Adjustable reflective sensor, Fixed transmissive sensor(Central aligned), Head-up sensor, Ribbon end sensor

MEDIA

Types: Roll-fed or Fan-fed,Die-cut or Continuous label,Tag stock,Continuous receipt paper

Width: 0.79"(20mm) - 4.65"(118mm)

Thickness: 0.003"(80um) - 0.007"(180um)

Label Roll Diameter: 5"(127mm)

Core Diameter:

1"(25.4mm),1.5"(38mm),3"(76.2mm)

RIBBON

Types: Wax,Wax/Resin,Resin

Width: 1.33"(33.8mm) - 4.33"(110mm)

Length: 984'(300m)

Core Diameter: 1"(25.4mm)

PHYSICAL CHARACTERISTICS

Dimension(L*W*H): 285*226*171mm

Weight: 2.26kg,excluding consumables