

Rugged Tablet PLUS E10 TL

Professional and rugged,
ideal for Logistics and Transportation,
Production, Retail and Hospitality.

Android 7
IP65, MIL-STD-810G
4G, WiFi 2.4GHz + 5GHz, Bluetooth 4.0 BLE, GPS, NFC
Bright Sunlight Viewable Display (400cd/m²)
Capacitive multi-touch supports glove touch, water rejection

OS
Android 7

CPU
MT8783 (8 core). 1.3GHz

Memory
2 GB / LPDDR3
16 GB / ROM EMMC

Display
10.1" 1280x800 IPS
400 nits tactile capacitive
10 point capacitive touch support
glove touch

RF
GSM
WCDMA / TD / SCDDMA
4G LTE
Wi-Fi 802.11 a/b/g/n/ac
Bluetooth V4.0
RFID HF/NFC
GNSS (GPS/GLONASS/QZSS)

Sensors & Data Collection

RFID/NFC
Gyroscope
E-Compass
G-Sensor
Gravity acceleration sensor
Light Sensor
Range Sensor
Control Button
Power ON/OFF
Volume +/-

Camera

2MP front camera
8MP rear camera with auto focus

Audio

Jack Audio x1
Embedded waterproof speaker x1

Dimensions and Weight

Support SDHC/SDXC x1 max: 64G
USB 2.0
hdmi 1. 4A
Support TF x1 max:128G
SIM x1
Power connector x1

Environmental

Operating temperature: -10°C to 50°C
Storage temperature: -30°C to 70°C
Humidity: 5% - 95%

Dimensions, Weight, Protection

268 x 178 x 14 mm
927g
IP65
MIL-STD-810G
Shock and vibration
Drop 1m
Outbox Accessories
Cigarette light adapter
Protect screen
Stylus

Inbox Accessories

USB Cable
OTG cable
Hand strap
Power adapter



Performance characteristics

Processor: Intel® Atom Quad-Core Z8350; 1.44-1.84GHz

System Memory: 4GB DDR3L RAM

Storage: Drive 64GB

Operating System: Windows® 10 (Professional or Home Edition 64-bit) or Android 5.1

Buttons: Volume +/-, power, barcode scanner trigger

I/O Board Configuration: USB, Micro USB, Mini HDMI, serial, ethernet, Support SDHC / SDXC (Up to 128GB), 3.5mm standard headphone Jack

Battery System: 37Wh, 3.7V, 10.000mAh; 6-8 hour battery life

Audio: Intel® HD audio, built-in microphone

Sensors: Gravity acceleration, light sensor

Scanner: High performance barcode scanner: 1D Zebra SE655 or 2D Honeywell N3680 (optional)

Camera: 5MP integrated (rear-facing) and 2MP integrated (front-facing)

Physical and environmental characteristics

Dimensions: 275 mm W x 180 mm H x 22.2 mm D

Display: 10.1-Inch Display, 1280 x 800

10-pt Projected Capacitive Touch; 320 nit

Weight: 1.24 kg - base configuration

Sealing: IP65 (water and dust)

Drop / Shock: MIL-STD 810G,

516.6 IV: 26 repeated 1,21 meters foot drops

225g ball drop to screen w/ protector from 100cm

Operating Temp: -20° C to +60° C

Storage Temp: -30° C to +70° C

Humidity: 95% non-condensing

Wireless & GPS network characteristics

Wireless: WiFi 802.11 a/b/g/n, 3G/4G LTE

Bluetooth:4.0

GPS: U-blox / BeiDou (included)

NFC: ISO/IEC 14443 13.56MHz technology (Optional)

Accessories

Dock station (3 USB, 1 Ethernet, DC 1 jack), delivered without power supply

Extra power supply (Compatible with the Dock)

Cigarette lighter charger

Locked support frame

VESA attach plate

DC / DC converter 9-36 V input, 5V output with terminal block

Screen protection

Removable 10000 mA 3.7V battery

Pen digitalizer delivered with a flashlight

Pen support

Handstrap

Power cable (for AT-CAE1005 converter)

Fixing cradle with supports

Ram Mount connector

DC jack power supply and microUSB

The Plus E10 TL Rugged Tablet is a strong and handy 10-inch tablet ideal for logistics and transportation, manufacturing, retail and hospitality. It can support many of the E2K solutions, such as E2K hotel, E2K food for Hospitality, E2K collect and E2K Retail.



Collect

Data collection for industrial uses.

