

Rugged Tablet PLUS RT 101

Professional and rugged,
ideal for Logistics and Transportation,
Production, Retail and Hospitality.



Testato MIL-STD 810G, a prova di caduta da 1,5 m
IP65, test di caduta da un metro
Batteria sostituibile a caldo, pacco batteria 10800 mAh integrato
Windows® 10 IoT Enterprise
Firmware TPM 2.0
Porta Ethernet 10/100

OS
Windows® 10

CPU
Intel® Atom™ X5-Z8550 Processor,
1,44 Ghz Quad Core

Memory
LPDDR3 4GB on board, MAX support 8G
64GB / 128GB eMMC

Display
10.1" WUXGA 1200x1920 IPS 470 nits
(Typ)

RF
Optional Sierra EM7455
4G LTE (optional)
GPS (onboard)
Wi-Fi 802.11a/b/g/n/AC
Bluetooth® 4.1

Camera
2Mp front camera
8Mp rear camera, autofocus, flash

Control Button
Power
Volume +/-
Reset home
Barcode scanner trigger
Sensor & Data Collection

Optional 1D/2D Barcode reader
9 Axis MEMS sensor (Accelerometer,
eCompass, Gyroscope)
Ambient Light Sensor
Proximity Sensor

Power Adapter
19V / 3.42A

Battery
Backup battery
Hotswappable external battery
Battery: 3.7V, 10800 mAh/40Wh
Battery operation: up to 8.5 hours

I/O Interface
Docking connector
Full size USB 3.0 x1
Full size USB 2.0 x1
Replaceable DC jack
Micro HDMI
3.5mm Audio jack
SIM card Reader
Micro SDXC Card reader
Reset hole

Dimensions Weight Protection
13.72"x7.56"x0.86"
(283.4mm x 192mm x 21.9mm)
2.64 lbs (1200g)

Durability

Fingerprint opzionale
Dock per veicoli, dock per ufficio, caricabatterie opzionale
Maniglia per valigetta, stilo, cinghia a mano opzionali
Banda larga mobile multi carrier 4G LTE opzionale
Lettori di codici a barre opzionali RFID / NFC / 2D
Honeywell per l'acquisizione dei dati

MIL-STD-810G (Multiple 5'/1.5m drops)
26 times all corners and sides with single tablet while operating"
IP65
500 times x 1m tumble test
Steel ball drop test, 25mm diameter rounded end steel weight of 250 gm from
50 cm w/screen protector
Glass screen protector

Accessories
Hand strap with stylus holder
Optional Capacitive stylus pen
Optional Vehicle dock
Optional office dock
Optional battery charger

Environmental
Operating temperature: -10°C to +50°C
Storage temperature: -20°C to +60°C

