PLURISERVICE S.P.A.

Pluriservice.it

Become a reseller for Pluriservice Spa!

Discover our Products!

PLUS APIX

Apix A.411

SELF-ADHESIVE LABEL APPLICATOR

APIX

Changes in the labeling, prestige and quality and reliability.
A self-adhesive label applicator for series A 411. Solid, sturdy, practical, versatile, suitable for all industrial applications. Accuracy and reliability, enhance the performance of labeling. A 411 in two versions by 120 mm and 180 mm of passage labels, with a speed of 20 or 30 meters per minute in a linear distribution.

eXatta G6.P2

PALLET PRINT AND APPLY

APIX

Rugged and reliable system.
Application on two contiguous sides of the pallet.
Automatic rotation of the label holder plate.

Apix 250S

APIX

Thermal transfer printer

"Thermal Smart Control" print technology produces cleanest, high quality barcodes
Print speed: Up to 356 mm (14") per sec.
Display: 4.3" color touch LCD panel with 6-button control
Small label peel off: up to 0.5 inch length
Interface USB host interface for stand-alone applications
Available in 203 dpi, 300 dpi and 600 dpi resolutions, firmware automatically detects printhead
resolution and switches accordingly
Ribbon: 600 meter ribbon

Plus 22.000

PLUS

Industrial Mobile Computer

Operating system: Android 7.0
Dimensions: 166 (L) × 73 (W) × 26 (H) mm
Weight: 330g (battery included)
Display: 4 "WVGA (800 × 480), capacitive touch screen
Keyboard Pad: 30 keys (side keys included) with backlight
Notifications: vibration, speaker and multicolored LEDs
Battery: 3.7V, 3700mAh
Camera: 8 megapixels, auto focus, with LED flashlight
Memory: 1GB RAM, 4GB ROM
Memory expansion: MicroSD card (max. 32GB) slot
Interfaces: Micro USB, RS-232C
Certification: IP65 withstands falls up to 1.2 m
Connectivity: Bluetooth, Wi-Fi, GPS, 4G
Google services

Plus 9700

PLUS

Industrial Mobile Computer

Display: 3,5" QVGA or VGA resitive touch
1D or 2D
standard or long range barcode scanning
Battery: 3600 mAh or 5400 mAh
OS: Microsoft Windows CE.NET 6.0 - Embedded Handheld 6.5.3 OR Android 6.0
Processor: TI OMAP 3730 1GHz
Wi-Fi: Cisco® CCXv4 Certified IEEE 802.11 a/b/g/n
Bluetooth®: Class II, V2.1 With Enhanced Data Rate (EDR)
Memory: 4GB Nand FLASH
512MB DDR SDRAM
Keyboard: 30 - 38 or 53 alphanumeric keys with blacklight
Pistol grip: available
Weight: 447g (3600 mAh) / 478g (5400 mAh)
Micro SD memory slot
IP 65

Pluriservice Spa - Via F. Santi, 22 - Z.Ind. Bassette - 48123 Ravenna (RA) ITALY - Tel. +39 0544 456669 - social capital fully paid: 1.000.000,00 € - commerciale@pluriservice.it

PLURISERVICE S.P.A.

Pluriservice.it

2 YEAR WARRANTY

Pluri Code

Pluricode 300

Direct thermal and thermal transfer printing applications
High printing speed(5IPS), fast label throughput
Double type sensors allowing to support broad range of labels
Dual-wall frame, robust and sturdy structure
TPH special designed overcoat, endure large printing volume
ZPL and TSPL programming language

Bundled with Bartender label designer software & Seagull Windows Driver
300-meter Ribbon Capacity
Resolution 203dpi(8dots/mm)
Printing Width 108mm Max
Printing Length 15mm - 1200mm
Optional cutter module
Optional Peeler module

€ 95,00* each

*MINIMUM 10 PIECES

Pluricode 330

Pluri Code

Scan mode: Automatic / handheld
Read speed: 250mm/sec
Resolution: 640(horizontal) x 480(vertical),256 gray levels
Scan angle: 45°(horizontal);30°(vertial)
Voltage: DC 5V±5%
Interfaces: RS232,USB
Operating temperature: -20°C ~ 60°C
Drop: Designed to withstand 1.8m drops
IP degree: IP54
Dimensions (LxWxH): 95mm×62mm×168mm
Weight: 136g

2D

€ 29,00* each

*MINIMUM 10 PIECES

Pluricode 7100E

Pluri Code

Omni Directional 2D Image Barcode Scanner
High sensitive image sensor Width 1024*Height*768
Good penetrability read all standard 1D/2D barcodes on mobile phone or paper, Plastic card and other printed media
32-bit processor, High decoding ability for easily reading poorly pronte and low quality barcodes
High-speed barcode identification without waiting
Resolution 4mil, Max Scan depth more than 650mm
Support self-upgrade, Convenient to update and customize
RS232, HID USB-KB, USB-COM Interfaces Supported

2D

€ 75,00* each

*MINIMUM 10 PIECES

Pluricode 323BT

Pluri Code

Processor type: 32Bit
scan mode: handheld
Memory: 16MB
Alarm mode: Red light alarm, Buzzer alarm
Resolution: 640(horizontal) x 480(vertial),256 gray levels
Scan angle: 45°(horizontal);30°(vertial)
Scan speed: 250mm/sec
Dimensions (LxWxH): 170mm×100mm×75mm
Weight: 150g (without cable)
Drop: Designed to withstand 1.8m drops
IP degree: IP54
Interfaces: Bluetooth 4.0, 2.4G ,USB
Communicate distance: Bluetooth 30m (in vacant space)
Light level: Visible Red light 630+10nm

2D

€ 79,00* each

*MINIMUM 10 PIECES

Ribbon

RIBBON RESIN/WAX INK OUT 110MM X 74 M
€ 0.45 PER RIBBON MINIMUM 1000 PIECES

RIBBON RESIN/WAX INK OUT 110MM X 360 M
€ 2.20 PER RIBBON MINIMUM 1000 PIECES



Labels

THERMAL TRANSFER LABELS 100 MM X 64 MM (600 LABELS PER ROLL) Ø 41 MM
€ 2,00 PER ROLL MINIMUM 512 PIECES

THERMAL TRANSFER LABELS 100 MM X 100 MM (1000 LABELS PER ROLL) Ø 72 MM
€ 4,00 PER ROLL MINIMUM 320 PIECES

ALL PRICES ARE VAT EXCLUDED

Pluriservice Spa - Via F. Santi, 22 - Z.Ind. Bassette - 48123 Ravenna (RA) ITALY - Tel. +39 0544 456669 - social capital fully paid: 1.000.000,00 € - commercialeweb@pluriservice.it