



Pluricode T3

Bluetooth Mobile Printer

Cod. STTTPC002




MAIN SPECIFICATIONS

- Support label printing and receipt printing
- Adjustable paper load, support label with different width
USB charging at your convenience
- Support various of 1D&2D barcode printing
- Multiple wireless interfaces, support iOS, Android, WinCE
- OLED display
- Long-lasting battery life (5 days stand-by)



OLED Display



Adjustable
Paper Guide



Rugged Design



Bluetooth



Travel



Logistic



Medical



Battery



Barcode



Windows



Android



iOS

Pluricode is a trademark of Pluriservice Spa

Via F. Santi, 22 - Z.Ind. Bassette 48123 Ravenna (RA) - Tel. +39 0544 456669 - Fax +39 0544 688954

Social capital fully paid: 1.000.000,00 € - commerciale@pluriservice.it



Pluricode T3

Bluetooth Mobile Printer

Cod. STTTPC002

Printing

Printing Method: Direct Thermal Line Printing
Resolution: 203dpi (8dots/mm)
Printing Speed: Max. 60mm/s
Printing Width: 72mm
Interface: USB, Bluetooth

POWER SAVING

Sleep Mode: yes

MEMORY

RAM: 4 MB
Flash: 8 MB

RESIDENT FONTS

Font: FONT A 12*24; FONTB 8*16;
CHN 24*24; 16*16;
Alphanumeric: 95
Codepage: 35

BARCODE

1D: UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39,
ITF, CODEBAR, CODE128, CODE93
2D: QR code, PDF417

GRAPHICS

Support bitmap printing with different density and
user defined bitmap printing

DETECTION

Sensors: Paper out/Black mark/Gap detection,
cover open switch

LED INDICATOR

Power Indicator: Green
Error Indicator: Red

RELIABILITY

TPH life: 50km

POWER

Input: AC 100-240V
Output: DC 5V/1A
Battery: 2000mAh/7.4V rechargeable Li-ion
battery

PAPER

Paper Type: Continuous paper, black mark
paper, die-cut or continuous label
Paper Width: 55-80mm
Paper Thickness: 0.053~0.15mm
Paper Roller Diameter: Max. 55mm
Paper Loading: Easy paper loading

PHYSICAL CHARACTERISTICS

Working Condition: -2°C~52°C, 30%~85%RH
Storage Condition: -20°C~70°C, 5%~90%RH
Dimension: 150(L)*120(W)*70(H)mm
Weight: 630g (including battery)

OPTIONS AND ACCESSORIES

Mini USB2.0 Cable, Charger, Paper
Roll, Quick Start Guide, CD, Belt Clip

SOFTWARE

Emulation: CPCL
Driver: Windows
SDK: WinCE, Win Mobile, Android, iOS

Pluricode is a trademark of Pluriservice Spa

Via F. Santi, 22 - Z.Ind. Bassette 48123 Ravenna (RA) - Tel. +39 0544 456669 - Fax +39 0544 688954
Social capital fully paid: 1.000.000,00 € - commerciale@pluriservice.it