




# Pluricode 201

Direct Thermal Receipt Printer



- Modern appearance design
- Faster printing speed, 6 inches 152mm/s Max., to improve the daily efficiency.
- 8MB SDRAM & 8MB Flash memory for a more flexible usage.
- Rich emulation language compatibility: TSPL, ZPL, EPL, DPL.



Pluricode è un marchio di Pluriservice Spa

Via F. Santi, 22 - Z.Ind. Bassette 48123 Ravenna (RA) - Tel. 0544 456669 - Fax 0544 688954  
Capitale sociale i.v.: 1.000.000,00 € - commerciale@pluriservice.it



# Pluricode 201

## Thermal Label Printer

### PRINTING FEATURES

**Resolution:** 203 DPI  
**Printing method:** Direct Thermal  
**Max.print speed:** 152 mm (6") / s Max.  
**Max.print width:** 104 mm (4.25")  
**Max.print length:** 1778 mm (70")

### MEDIA

**Media type:** Continuous, gap, black mark, fan-fold and punched hole  
**Media width:** 25.4 mm ~ 118 mm (1.0"-4.6")  
**Media thickness:** 0.06~0.25 mm (2.36~9.8mil)  
**Media core diameter:** 25.4 ~ 76.2 mm (1"~ 3")  
**Label length:** 10 mm ~1778 mm

### PERFORMANCE FEATURES

**Processor:** 32-bit CPU  
**Memory:** 8MB Flash Memory, 8MB SDRAM, Flash memory can be expanded to Max. 4 GB  
**Interface:**  
Standard version: USB  
Optional: Lan/WIFI/Bluetooth/TF card  
**Sensors:** Gap sensor; Cover opening sensor; Black mark sensor

### FONT/GRAPHICS/SYMBOLOLOGIES

**Internal fonts:** 8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.

#### 1D bar code

Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GSI DataBar, Code 11

#### 2D bar code

CODABLOCK F mode, DataMatrix, Maxicode, PDF-417, Aztec, MicroPDF417, QR code, RSS Barcode (GSI Databar)

**Rotation:** 0°, 90°, 180°, 270°

**Emulation:** TSPL, EPL, ZPL, DPL

### PHYSICAL FEATURES

**Dimension:** 215 mm (L) x 178 mm (W) x 149.5 mm (H)  
**Weight:** 1.32 kg

### RELIABILITY

**Warranty:** One year  
**Print head life:** 30 km

### SOFTWARE

**Driver:** Windows/ Linux/ Mac  
**SDK:** Windows/ Android/ iOS

### POWER SUPPLY

**Input:** AC 100-240V  
**Output:** DC 24V-2.5A

### OPTIONS

**Factory Options:** Lan - Bluetooth - WIFI - TF card - RTC - Peeling machine - Cutter

#### Dealer Options:

External paper roll holder  
Paper roll spindle  
Extension board for external paper roll holder

### ENVIRONMENTAL CONDITIONS

#### Operation environment:

5 ~ 40°C (41~104°F) Humidity: 25 ~ 85% no condensing

**Storage environment:** -40 ~ 60°C (-40~140°F) (Humidity: 10 ~ 90% no condensing)

Pluricode è un marchio di Pluriservice Spa

Via F. Santi, 22 - Z.Ind. Bassette 48123 Ravenna (RA) - Tel. 0544 456669 - Fax 0544 688954  
Capitale sociale i.v.: 1.000.000,00 € - commerciale@pluriservice.it