



PLUS

PLUS 25 III



Thermal Transfer/ Direct Thermal



Plus 25 III black
Cod. STTTPL001

Plus 25 III white
Cod. STTTPL002

- Print speed up to 127mm/s
- Ribbon roll capacity 300m (**Ribbon Ink Out**)
- Support TSPL, EPL, ZPL, DPL commands
- Support multiple material printing





PLUS 25 III

Thermal Transfer/ Direct Thermal

MODEL

Resolution: 203 DPI

Print method: Thermal Transfer / Direct Thermal

Print speed: 127 mm (5") / s Max.

Max.print width: 104 mm (4.09")

Max.print length: 1778 mm (70")

MEDIA

Media type: Continuous, gap, black mark, fan-fold and punched hole

Mediawidth: 25.4~118mm (1.0"~4.6")

Media thickness: 0.06-0.254 mm (0.0023" ~ 0.01")

Media Length: 10 ~ 1778 mm (0.39" ~ 70")

Media roll capacity: 127mm (5") OD (Outer Diameter)

Support core diameter: 1 in./25.4 mm

Tape capacity: Max. 300 m

Ribbon Width: 25.4mm-110mm

PERFORMANCE FEATURES

Memory: 8 MB RAM / 8 MB Flash Memory

Interface: USB, USB+Serial, USB+Lan, USB+Serial+Lan

Optional: Bluetooth/Wi-Fi

Sensors: Black Mark Sensor/Gap Sensor

FONTS/GRAPHICS/SYMBOLOGIES

Internal fonts: Font 0 ~ Font 8

1D barcode: Code 39, Code 93, Code 128UCC, Code 128, subset A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN e UPC con aggiunta di 2(5) cifre, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11

2D barcode: PDF-417, Maxicode, DataMatrix, QR code, Aztec

Emulation: TSPL,ZPL,EPL,DPL

PHYSICAL FEATURES

Dimension: 282 mm (D) x 232 mm (W) x 171 mm (H)

Weight: 2.56 kg

RELIABILITY

Print head life: 30 km or 1 year

SOFTWARE

Driver: Windows / Linux / Mac / Android /Chrome OS

SDK: Windows / Linux / Android / iOS

Software: Bartender UltraLite / Mobile Label Design App

POWER SUPPLY

Input: AC 110-240V, 1.8A, 50-60Hz

Output: DC 24V, 2.5A, 60W

OPTIONS

Factory Options: Bluetooth module, WiFi module, peeler, cutter
Communication interface RS-232C (2400-115200 bps)

Dealer Options:

8" External paper roll holder

ENVIRONMENTAL CONDITIONS

Operation: 5 ~ 40°C (41~104°F), Humidity: 25 ~ 85% non-condensing

Storage environment: -40 ~ 60°C(-40~140°F), Humidity:10 ~ 90% non-condensing